



SHELL ADVANCE RACING ENGINE OIL 4T 5W-20

Application

Shell Advance Racing Engine Oil 4T 5W-20 is a high performance 4-stroke lubricant designed for use in racing bike engines in the Supersport World Championship.

Specifications

This product has been used in Superbike and Supersport applications.

Characteristics

Designed for high performance 4-stroke racing engines

- Maximum power with excellent protection
- Excellent shear stability
- Suitable for wet clutches

Health, safety and environment

Shell Advance Racing Engine Oil 4T 5W-20 is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

For further guidance on Product Health and Safety refer to the appropriate Shell Product Safety Data Sheet.

Protect the environment. Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Physical characteristics

Viscosity Grade	SAE 5W-20	
Kinematic Viscosity	@ 40°C	51 mm ² /s
	@ 100°C	9 mm ² /s
Viscosity Index	161	
Dynamic Viscosity	@ -25°C	3,060 mPas
Density	@ 15°C	0.852 kg/l
Flash Point	PMCC	220°C



These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur. July 2004